

3"/4"

Gimbal Spot Float Can-less Recessed Downlight with 5CCT Selector

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

GIMBAL SPOT FLOAT

The **MFGD-SP Series** Canless Spot Float Gimbal downlight is designed to highlight the architectural and artistic elements in your home. It features adjustment of 80-degree tilt, 360-degree rotation, fully dimmable and 95 CRI rating (color rendering index). With the canless design, it no longer requires a recessed housing for the installation, allows you to install it almost anywhere. These recessed down lights are also designed for use in new construction, remodel and retrofit installation without needing a housing or j-box.


Perfect use for residential housings, condominiums, the healthcare facility, shopping centers and hospitality industry.



Select color temperature from

- 2700K **WARM WHITE**
- 3000K **SOFT WHITE**
- 3500K **NATURAL WHITE**
- 4000K **COOL WHITE**
- 5000K **DAYLIGHT**

DIMENSION



MODEL#	MFGD036-SP	MFGD049-SP
A	1.22"	1.5"
B	3.78"	5"

Energy Star® and ETL certified. It can be used to comply with Title-24 and JA8 high efficacy light source requirements.

TECHNICAL SUMMARY

MODEL #	LUMENS	WATTS	EFFICACY	CRI	VOLTAGE	BEAM °	CCT	PF	LIFE	OPERATING TEMP.
MFGD036-SP-5CCT-WH	345	6W	58 lm/W	90	120V, 60 Hz	60°	2700K/ 3000K/ 3500K/ 4000K/ 5000K	>0.9	50,000 hrs	-5°F ~ 104°F
MFGD049-SP-5CCT-WH	540	9W	60 lm/W							

PART NUMBER ORDERING SUMMARY

I	M	F	G	D	04	9	-	SP	-	5CCT	-	WH
IUS	M Mfg	F Float	G Gimbal	D Downlight	3"/4" Aperture	6W/9W Wattage		SP Spot Float		5CCT 27K/30K/35K/40K/50K		WH White

**3"/4"****Gimbal Spot Float Can-less Recessed Downlight with 5CCT Selector**

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

CONSTRUCTION

Unit includes spinning metal housing, LED array, heat sink, lens, and foam gasket with deep baffle white ring.

OPTICS

- High quality PC lens
- Efficiency LED array
- Diffuse for uniform illumination

DRIVER

- High efficiency integral 120V 60Hz constant current dimmable driver.
- Smooth flicker free deep dimming to 10%

MOUNTING

- Can-less design, no can housing needed for the installation
- Pre-installed surface mounting bracket adapter
- Junction box included
- Ceiling mount, directly mount on drywall

LISTING

ETL Listed, Energy Star Listed, Suitable for Wet Locations, Title 24 JA8-2022, RoHS, Air-Tite Certified

WARRANTY

5 years manufacturer warranty, consult factory for more details. Terms and conditions may apply.

**360° AND 80°**

These recessed light can be rotated 360° and tilt up to 80°. Easy for you to adjust the angle and direction after the installation.

COMPATIBLE PRODUCTS (SOLD SEPARATELY)**MRSDMP-346**

Mounting plate for 3"/4"/6" can-less downlight

**M3FTCABLE
M10FTCABLE**

3ft/ 10ft Extension cord for can-less downlight

RECOMMENDED DIMMERS**LUTRON**

- TGCL-153PH-WH
- DVCL-153PR
- P-PKG1W-WH-R
- CTCL-153PDH-WH

LEVITON

- R00-RNL06-TW
- R50-IPL06-10M

