

6" Commercial Grade Recessed Downlight with Wattage and 3CCT Selector

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

COMMERCIAL DOWNLIGHT

The **M6CDLA20W** downlight fixture is an all-in-one solution for your commercial recessed applications. The color temperature can be switched from 3000K soft white, 4000K cool white to 5000K daylight and the lumen can be adjusted to 3 different levels. Also, the canless design reduce the required of clearance for the installation. The M6CDLA20W downlight is Energy Star® and UL certified.



Perfect use for shopping center, business building, hotel, airport, hospital and other commercial buildings.



Select color temperature from

- 3000K **SOFT WHITE**
- 4000K **COOL WHITE**
- 5000K **DAYLIGHT**

DIMENSION



Energy Star® and ETL certified. It can be used to comply with Title-24 and JA8 high efficacy light source requirements.

TECHNICAL SUMMARY

MODEL #	LUMENS	WATTS	EFFICACY	CRI	VOLTAGE	BEAM °	CCT	PF	LIFE	OPERATING TEMP.
M6CDLA20W-3CCT	1140/ 1520/ 1900	12W/ 16W/ 20W	95 lm/W	80	120V- 277V, 60 Hz	110°	3000K/ 4000K/ 5000K	>0.9	50,000 hrs	-5°F ~ 104°F

PART NUMBER ORDERING SUMMARY



6"

Commercial Grade Recessed Downlight with Wattage and 3CCT Selector

ILLUMINATING US
lighting

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

CONSTRUCTION

Unit includes die-cast metal housing, LED array, heat sink, lens, foam gasket, baffle trim ring, safety cable with hook and junction box.

OPTICS

- High quality PC lens
- Efficiency LED array
- Diffuse for uniform illumination
- Baffle trim reduces glare for soft, comfortable illumination

DRIVER

- 120V-277V 60Hz universal input voltage
- 0-10V smooth flicker free dimming to 5%

MOUNTING


- Canless design, no can housing needed for the installation
- Pre-installed torsion spring clips
- Unit comes with wiring nuts, no electrical tap and special tools required for the installation

LISTING

ETL Listed, Energy Star Listed, Suitable for Wet Locations, Title 24 JA8-2022, RoHS, Air-Tite Certified

WARRANTY

5 years manufacturer warranty, consult factory for more details. Terms and conditions may apply.

PHOTOMETRY

Maximum Candela = 653.88 Located At Horizontal Angle = 112.5, Vertical Angle = 1
 # 1 - Vertical Plane Through Horizontal Angles (112.5 - 202.5) (Through Max. Cd.)
 # 2 - Vertical Plane Through Horizontal Angles (0 - 180)
 # 3 - Horizontal Cone Through Vertical Angle (1) (Through Max. Cd.)

RECOMMENDED DIMMERS**LUTRON**

- TGCL-153PH-WH
- DVCL-153PR
- P-PKG1W-WH-R
- CTCL-153PDH-WH

LEVITON


- R00-RNL06-TW
- R50-IPL06-10M

COMPATIBLE PRODUCTS (SOLD SEPARATELY)**MRSDMP-346**

Mounting plate for 3"/4"/6"
can-less downlight

**MRSDMP-468**

Mounting plate for 4"/6"/8"
can-less downlight

**MHV-8W-EM**

Emergency Driver and
Battery Back-up

**MHV-25W-EM**

High Output Voltage Emer
gency Driver and Battery
Back-up

IUS
lighting

www.illuminatingus.com

ILLUMINATING US, LLC

813 W Elgin St Broken Arrow, OK 74012

TEL: 918-804-7618 E-mail: Info@illuminatingus.com