

8' LED Commercial Vaportight with Wattage and CCT Selector



65-75-90 WATTS

The IMVP8FT-65-75-90W-3CCT series

This Vapor Tight Fixtures are designed to save energy and meet low light egress requirements. It's optimal for underground parking garage compliance. Also, it's perfect for using as utility lighting, parking garage and stairwell lighting where meets applicable building and safety codes. These fixtures are DLC and UL certified. They are popular in parking lot, warehouse, public area and other commercial area.
















Select color temperature from

- 3500K NATURAL WHITE
- 4000K COOL WHITE
- 5000K DAYLIGHT



DIMENSION



TECHNICAL SUMMARY

LUMENS	WATTS	EFFICACY	CRI	VOLTAGE	BEAM °	сст	PF	LIFE	OPERATING TEMP.
8450 9750 11700	65W 75W 90W	130 lm/W	80	120V, 277V	140	3500К 4000К 5000К	>0.9	100,000 hrs	-40°F ~ 104°F

PART NUMBER ORDERING SUMMARY





8' LED Commercial Vaportight with Wattage and CCT Selector

Project Name:	Order Number:	Prepare by:	Note:	Date:	Туре:

CONSTRUCTION

- Unit includes heavy duty plastic frame, LED array, heat sink, and lens.
- · High quality PC lens.
- · Efficiency LED array.
- · Diffuse for uniform illumination.
- CRI 80+

DRIVER

- 120-277V universal input voltage.
- 0-10V smooth flicker free dimmable.

MOUNTING

- Pendant Mount with V-Hook
- · Surface mounting

LISTING

- DLC Listed
- UL 1598 suitable for wet locations
- UL 8750 LED equipment in Lighting Products

WARRANTY

5 years manufacturer warranty

* Terms and conditions may apply.

*5 years limited LED luminaire warranty to the original purchaser that the luminaire shall be free from defects in mate-rials and workmanship from date of shipment, when under properly installed at normal conditions of use. The warranty may not cover physical damage or abuse under certain conditions.

ACCESSORIES (SOLD SEPARATELY)



MHV-8W-EM

- Input Voltage 120-277V
- 8W Output
- Output Voltage 150-200Vdc



MHV-25W-EM

- Input Voltage 120-347V
- 25W Output
- Output Voltage ≤ 175Vdc

OCCUPANCY SENSORS (SOLD SEPARATELY)



MBRI819-B-0 120-277v On/off Passive Infrared Occupancy Sensor



MBRI819-B-D Bi-level passive infrared Occupancy sensor

