

DUAL HEADS EMERGENCY LIGHT

| Project Name: | Order Number: | Prepare by: | Note: | Date: | Type: |
|---------------|---------------|-------------|-------|-------|-------|
| | | | | | |

The Round Dual Heads Emergency Light delivers bright, dependable lighting during power outages or emergency situations. Equipped with two fully adjustable LED heads, it allows precise directional illumination where it's needed most. Its energy-efficient LED technology provides up to 150 lumens per head while maintaining long-lasting performance. The unit features a durable thermoplastic housing, easy wall or ceiling mounting, and a built-in rechargeable battery to ensure lights remain operational when the main power fails. Ideal for residential, commercial, and industrial applications, this emergency light enhances safety and compliance in hallways, stairwells, offices, and public spaces.







DIMENSION



Dual Adjustable LED Heads

Provides bright, focused illumination during power outages for enhanced safety and visibility.

Reliable Backup Power

Built-in rechargeable battery automatically activates during outages to ensure continuous lighting.

TECHNICAL SUMMARY

| MODEL # | NAME | VOLTAGE | COLOR | BATTERY | RECHARGE TIME | EMERGENCY OPERATION | LED CHIPS | WATTAGE | LUMEN | CRI |
|---------|-------------------------------|----------|-------|------------------|------------------|---------------------|--------------|---------|-------|-----|
| IMJ-10L | DUAL HEADS EMERGENCY LIGHT | 120/277V | N/A | build-in 3.6V | ≤24hrs | ≥90mins | 24 | 2.4W | 150LM | 80 |

ELECTRICAL

- •120/277V voltage operation. Optional multi-tap voltage available.
- Built-in 3.6V 700mAH rechargeable Ni-CD battery for minimum 90 minutes emergency operation
- · Maximum 24 hours for full recharge time.
- Test switch and charge indicator.

MOUNTING

- · Innovative, easy installation in minutes.
- Universal pattern on back plate for wall mount.

HOUSING

- Injection-molded, engineering grade. 5VA flame retardant.
- ${\boldsymbol \cdot}$ High-impact resistant, thermoplastic in white or black finish.

WARRANTY/LISTING

- Two years warranty on all electronics and housing. Battery two years warranty for battery meets UL 924.
- cUL and UL listed for damp location (0°C-40°C).

