

RECESSED REMODEL HOUSING Series

4"/6" Remodel Construction Shallow Housing


Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

The **608-SH-RM/408-SH-RM** IC type remodel shallow can housings is designed for both ceiling joists installations and drop ceiling (with T-bar grid) installations. It can be completely covered by thermal insulation. Also, the fixture may direct contact with any combustible material like ceiling joist or floor board safely.

The 608-SH-RM/408-SH-RM is a Title 24 compliant, no screw based socket or other medium-based incandescent socket adapters are needed.



DIMENSION



MODEL#	608-SH-RM	408-SH-RM
A	5.5"	4.62"
B	6.75"	4.75"
C	9.75"	7.75"

CONSTRUCTION

- Metal housing and frame
- Extendable hanger bar
- Foam gasket included
- Pre-installed nails for easier installs in lumber and woods
- Title 24 compliant

JUNCTION BOX

- Quick wiring connectors included for easier wiring, no wiring nuts and electrical tap needed
- Eight conduit knockouts for convenient wiring

MOUNTING

- Unit is for remodel construction fixture, designed to be installed in applications where the ceiling joists are exposed
- Unit can be installed onto a drop ceiling with T-bar grid in place
- Can be completely covered by thermal insulation
- May direct contact with any combustible material like ceiling joist or floor board

LISTING

- ETL certified
- Air-Tite certified per ASTM-E283
- Suitable for damp locations
- Certified to California JA8
- Can be used to comply with Title 24 Part 6 requirements

WARRANTY

5 years manufacturer warranty, consult factory for more details. Terms and conditions may apply.