IMJB04-9W-5CCT



4" LED Multi Fit Recessed Downlight

| Project Name: | Order Number: | Prepare by: | Note: | Date: | Type: |
|---------------|---------------|-------------|-------|-------|-------|
| | | | | | |

This 4" Multi Fit LED light (9W) designed for J-Box or can retrofit installations, offering a sleek recessed look with a very thin trim and optional magnetic color trims. It is IC rated, air-tight, ETL certified, and safe for wet locations like showers and outdoor areas. The fixture features 5 selectable color temperatures (2700K–5000K), outputs 700 lumens (equivalent to 50W halogen), has a 110° beam angle, 90+ CRI, supports TRIAC dimming (10–100%), and operates in -4°F to 104°F. With a projected life of 50,000 hours (at 70% light output) and a 5-year warranty, it meets fire rating code when used with a fire-rated J-box.
















DIMENSION





TECHNICAL SUMMARY

| MODEL NO. | WATTS | LUMENS | CCT | VOLTAGE | DIMMING | CRI | BEAM ANGLE |
|----------------|-------|--------|-----------------|-------------|---------------|-----|------------|
| IMJB04-9W-5CCT | 9W | 700LM | 27/30/35/40/50K | AC120V-60HZ | TRIAC 10-100V | 90 | 110° |

PART NUMBER ORDERING SUMMARY



IMJB04-9W-5CCT



4" LED Multi Fit Recessed Downlight

| Project Name: | Order Number: | Prepare by: | Note: | |
|---------------|---------------|-------------|-------|--|
| | | | | |

CONSTRUCTION

- Durable aluminum construction
- Polycarbonate frosted lens

OPTICS

- Diffuse for uniform illumination.
- CRI 90

DRIVER

- 120 60Hz universal input voltage
- TRIAC 10-100V

MOUNTING

Installs in j-box mount or Retrofit

LISTING

- IC Rated
- ETL

WARRANTY

5 years manufacturer warranty,

* Terms and conditions may apply.

*5 years limited LED luminaire warranty to the original purchaser that the luminaire shall be free from defects in mate-rials and workmanship from date of shipment, when under properly installed at normal conditions of use. The warranty may not cover physical damage or abuse under certain conditions.

HIGHLIGHT



Durable Construction

Aluminium housing with a polycarbonate frosted lens.

Wide 110 Beam Angle

Delivers even, general illumination.

